

FEATURES

- * 4CH Display Resolution 1080P / 1080P
- * Recording Resolution 1080P
- * 4TB HDD, VGA, HDMI & 2USB
- * High Definition output (1920 X 1080)
- * P2P Cloud Function



SPECIFICATION

Model	AX-HDXVR7204P
Main Processor	Technical grade embedded microprocessor HI 3520D, Embedded LINUX operating system
Display Screen	1/4 screen (take analog channel as an example, other is base on the selected channel mode)
Video Standard	PAL(625 lines,50fps);NTSC(525lines,60fps)
Monitor Quality	VGA: HD; HDMI: HD
Encode Capability	Local analog Input: 4*1080:4*AHD-L
	Local analog + network digital input : 2*1080P (analog) +2*720P (IP)
	All network digital input : 4*1080P ; 4*1080P ; 8*1080P ; 8*1080P ; 1*1080P
Decode Capability	1*1080P
Motion Detection	Each channel can set 192(16*12)detection area;can set multi-level of flexibility (for local analog channel only)
Record Mode	manual>alarm>motion detection>timing
Local Playback	4CH playback synchronously
Video Search	time,date,event,channel search
Space Occupation	720P 20G/day ; 960H 12~20G/day*ch ; audio : 691.2M/day*ch
Video Storage	Local HDD ,Network
Backup Mode	Network backup,USB portable HDD,USB imprint,
Video Input	4CH BNC
Video Output	1ch VGA,1ch HDMI(support1920*1080P)
Audio Input	4CH
Audio Output	1CH
Alarm Input	NO
Network Port	RJ45 10/100Mbps adoptive Ethernet Network Port
PTZ Control	1 RS485;support multi kinds of PTZ protocol
USB Port	2*USB2.0
HDD Port	1* SATA ports(biggest 4TB)
Network Function	HTTP, TCP/IP, IPv4/IPv6,UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS
Client Monitoring	CMS , WebCC, Free DDNS, Cloud P2P
Smart Phone	iPhone, iPad, Android
Control equipment	Mouse and Remote Control
Operating Temperature	0% ~ 55%
Working humidity	10% ~ 90%
Air pressure	86kpa ~ 06kpa
Power Supply	DC 12 V 2 Amps
Dimensions (WxHxD)	310x45x200mm(W*H*D)
Weight	2.1 KG without HDD (Approximately)

Itan Thiulla Paaraiyirunthu Yethuvum Thappa Mudiyaathu

Design & Specifications are subject to change without Prior notice

