

**Features**

- \* 3 Mega Pixels Full HD Network IR Bullet Camera
- \* 1/2.5" SONY Exmor CMOS Sensor
- \* 3 Mega Pixel 5 ~ 50mm Varifocal HD CS Lens
- \* Infra Red LED 5 μm X 42 Pcs
- \* Built-in POE 802.3af
- \* ONVIF 2.0
- \* WDR, Day/Night(ICR), 3DNR,AWB,AGC,BLC
- \* Advanced H.264 High profile compression
- \* Support Several Servers, CMS, IP Address, DDNS, FTP, SMTP
- \* Support iPhone, iPad, Android, Windows Phone
- \* Support Single, Dual streams, Low streams and high resolution image
- \* IP 66 Class (High Pressure Water Jets from any Direction)



**Specification**

| Model                    | AXI-IPC-B60S3360WDR  |
|--------------------------|--|
| Sensor                   | 1/2.5" SONY Exmor CMOS Sensor  |
| Mega pixel               | 3 Mega pixel   |
| Effective Pixels         | 2052(H) X 1536(V)  |
| Lens                     | 3 Mega Pixel 5 ~ 50mm Varifocal HD M12 Lens  |
| IR LED                   | Infra Red LED 5 μm X 42 Pcs  |
| IP CLASS                 | IP66   |
| IR Range Distance        | 60 Meters Range  |
| IR CUT                   | Yes  |
| Minimum Illumination     | Color: 0.02 Lux/F1.4, B/W : 0.01Lux/F1.4; 0Lux/F1.2(IR on)   |
| Electronic Shutter Speed | Auto/Manual, 1/3~1/10000s  |
| Back Light Comp.         | BLC / HLC / WDR  |
| POE                      | Built-in POE 802.3af   |
| Noise Reduction          | 3D   |
| Privacy Masking          | Up to 4 areas  |
| Video Processing         | H.264 Video Code, Support dual-stream, 32k-8m adjustable, 1-30/s frame rate adjustable                                     |
| Video Resolution         | 3.0M(2048×1536) / 1080P(1920×1080) / 720P(1280×720) / D1(704×576) / CIF(352×288)   |
| Main Stream              | 3M(1~15fps)/1080P/720P(1 ~ 25/30fps)   |
| Sub Stream               | D1/CIF(1 ~ 25/30fps)   |
| Standard protocol        | Onvif 2.3  |
| Network Port             | 1 RJ45 Ethernet interface, 10/100M adaptation  |
| Network Protocol         | TCP/UDP/HTTP/MULTICAST/UPnP/NTP/RTSP/Onvif   |
| Delay                    | Within the LAN 0.3S  |
| Frame Rate               | 25/30 FPS adjustable   |
| Bit Rate                 | H.264: 32K ~ 8192Kbps, MJPEG: 32K ~ 24576Kbps  |
| Video Compression        | H.264/JPEG, support AVI format.  |
| Operation Function       | Support Web setting, OSD, real-time video transmission, motive detection and IO alarm; support MJPEG capture, CMS platform |
| Mobile Phone Monitor     | iPhone, iPad, Android, Windows Phone   |
| Power Supply             | DC12V(AC24 optional), PoE(802.3af)   |
| Working Temperature      | .-20°C~60°C  |
| Humidity                 | 0% -90% RH, Without Condensation   |
| Color/Material           | White / Alloy Metal  |
| Dimensions(W×H×D)        |  |
| Weight                   | 1 Kilo Gram (Approximately)  |