



AXI-IPC-DFS2220S

- * 2 Mega Pixels Full HD Network IR Dome Camera
- * 1/2.5" Sony Image CMOS Sensor
- * 3 Mega Pixel 3.6mm HD M12 Lens
- * Infra Red 5µm X 36Pcs
- * Built-in POE 802.3af & ONVIF 2.3
- * Micro SD Memory
- * DWDR, Day/Night(ICR), 3DNR,AWB,AGC,BLC
- * Advanced H.264 High profile compression
- * Support Several Servers, CMS, IP Address, DDNS, FTP, SMTP
- * Support iPhone, iPad, Android
- * Support Single, Dual streams, Low streams and high resolution image



Specification

Model	AXI-IPC-DFS2220S
Image Sensor	1/2.5" Sony Image Sensor
Mega pixel	2 Mega pixel
Effective Pixels	1920(H) X 1080(V)
Lens	3 Mega Pixel 3.6mm HD M12 Lens with Angle of view 85°
IR LED	Infra Red LED 5µm X 36 Pcs
IR Range Distance	20 Meters Range
IR CUT	Yes
Minimum Illumination	Color: 0.02 Lux/F1.4, B/W: 0.01Lux/F1.4; 0Lux/F1.2(IR on)
Electronic Shutter Speed	Auto/Manual, 1/3~1/10000s
Back Light Comp.	BLC / HLC / DWDR
PoE	Built-in PoE 802.3af
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Video Processing	H.264 Video Code, Support dual-stream, 32k-8m adjustable, 1-30/s frame rate adjustable
Video Resolution	1080P(1920×1080) / 720P(1280×720) / D1(704×576/704×480) / CIF(352×288/352×240)
Main Stream	1080P/720P(1 ~ 25/30fps)
Sub Stream	D1/CIF(1 ~ 25/30fps)
Standard protocol	Onvif 2.3
Network Port	1 RJ45 Ethernet interface, 10/100M adaptation
Network Protocol	TCP/UDP/HTTP/MULTICAST/UPnP/NTP/RTSP/Onvif
Delay	Within the LAN 0.3S
Frame Rate	50Hz: 25fps(1920 × 1080), 25fps (1280 × 960), 25fps (1280 × 720) 60Hz: 30fps(1920 × 1080), 30fps (1280 × 960), 30fps (1280 × 720)
Bit Rate	H.264: 32K ~ 8192Kbps, MJPEG: 32K ~ 24576Kbps
Video Compression	H.264/JPEG, support AVI format.
Operation Function	Support Web setting, OSD, real-time video transmission, motive detection and IO alarm; support MJPEG capture, CMS platform
Mobile Phone Monitor	iPhone, iPad, Android
Power Supply	DC12V(AC24 optional), PoE(802.3af)
Working Temperature	.-20°C~60°C
Humidity	0%-90% RH, Without Condensation
Color/Material	White / Polycarbonate
Dimensions(W×H×D)	100mm X 105mm X 105mm
Weight	400 Gram (Approximately)
Certi?cations	CE FCC RoHs STQC

Design & Specifications are subject to change without Prior notice

Nothing Can Escape from the Altrox Eye

