



## AX-NVR-5516-5P

- ★ 16 Channel Enterprises Network Video Recorder
- ★ Support 16 CH 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P IP Input
- ★ Up to 8 Mega pixels resolution recording
- ★ Support H.265+ / H.264 Compression Video Formats
- ★ Accurate retrieval, instant playback
- ★ Support HDD hot swap with RAID1, 5 Storage Scheme Configurable
- ★ 1 SATA HDD Bay with up to 10TB for each HDD
- ★ Support various VCA detection alarm and VCA search
- ★ Support for P2P, UPnP, NTP, DHCP, PPPoE
- ★ Support for mobile client access



### Specification

<b>Model</b>	<b>AX-NVR-5516-5P</b>
<b>System</b>	
Compression	Standard H.265+
Main Processing Chip	ARM Cortex A17
OS	Embedded Linux
<b>Video</b>	
Network Access Bandwidth	256Mbps
Input Resolution	8MP \ 5MP \ 4MP \ 3MP \ 1080P \ 960P \ 720P Real Time
Network Access	16 CH IPC input
Output	HDMI×1:3840×2160/1920×1080/1280×1024/1024×768 VGA×1:1920×1080/1280×1024/1024×768
<b>Audio</b>	
Input	16 CH IPC audio input
2-way Audio	RCA×1
Local Output	RCA×1
<b>Record</b>	
Resolution	8MP \ 5MP \ 4MP \ 3MP \ 1080P \ 960P \ 720P
Frame Rate	25FPS / 30FPS (PAL/NTSC)
Bite Stream	32Kbps-12Mbps
Image Quality	5 Level
<b>Playback</b>	
Simultaneous Playback	Max 16 CH
<b>Network</b>	
Interface	RJ45 10/100/1000 Mbps x 1; RJ45×16 (PoE Port)
Network Protocol	TCP/IP \ PPPoE \ DHCP \ DNS \ DDNS \ UPnP \ NTP \ SMTP \ ONVIF \ GB28181
<b>Storage</b>	
HDD	1 SATA
Max Capacity for HDD	10 TB
<b>Backup</b>	
USB Backup	Yes
eSata Backup	No
<b>Interface</b>	
Alarm In	1
Alarm Output	1
Communication	RS485×2, connect to PTZ and keyboard
Remote	Optional
USB	USB2.0×1 (Front panel), USB3.0×1 (Rear panel)
<b>Others</b>	
Case	2 U
Dimensions(mm )	440×390×70(W×D×H)
Power Supply	ATX
Consumption	? 30W ( without HDD )
Work Environment	-10 □ 50 □ 10% □ 90% humidity

Design & Specifications are subject to change without Prior notice

Nothing Can Escape from the Altronx Eye

